


# PROLITE

## OUTDOOR MOVING MESSAGE

character height  
6cm up to 54cm

readability 30m up to  
270m



type	character height (cm)	characters on display	readability in m	LEDs per pixel	dimension w x h x d (cm)
DL-060BR20	6	20	30	1	120 x 17 x 10
DL-060BR33	6	33	30	1	190 x 17 x 10
DL-100BR20	10	20	50	2	185 x 20 x 10
DL-100BR33	10	33	50	2	305 x 20 x 10
DL-140BR20	14	20	70	4	270 x 25 x 10
DL-140BR33	14	33	70	4	440 x 25 x 10
DL-180BR20	18	20	90	6	325 x 30 x 10
DL-180BR33	18	33	90	6	535 x 30 x 10
DL-270BR20	27	20	135	12	490 x 45 x 10
DL-270BR33	27	33	135	12	810 x 45 x 10
DL-400BR20	40	20	200	21	700 x 60 x 10
DL-400BR33	40	33	200	21	1150 x 60 x 10

### Specifications

- illumination characters in red
- viewing angle 120°
- case colour blanc anodised
- software DxSys up to Windows XP
- interface RS-232

### Optional

- case in a different RAL colour
- DX-LAN network server
- DX-WCM bluetooth modem
- DX-GSM mobile modem
- other illumination colours on request